



NOTE:
 SURFACE MOUNTED UNIT SHALL BE ATTACHED WITH NO LESS THAN 3 CONCRETE ANCHORS WITH A MINIMUM DIAMETER OF 3/8" AND A MINIMUM LENGTH OF 4" LONG. THE EMBEDDED DEPTH SHALL BE A MINIMUM OF 3 3/8". THE ALLOWABLE TENSION LOAD SHALL BE 2,270 LBS. WHEN INSTALLED IN NORMAL WEIGHT, 3,000 PSI CONCRETE

UNASSEMBLED ISOMETRIC VIEW

centroid - C	maximum sign area - A
7 ft	15.0 sq. ft.
8 ft	13.4 sq. ft.
9 ft	11.9 sq. ft.
10 ft	10.7 sq. ft.
11 ft	9.7 sq. ft.

PAGE: 1 of 1

DRAWING# 16.407	PROJECT# ...	SCALE: ...	Division of Dakota Fence
DRAWN BY: ...	DATE: 11/9/16	REVISED: 12/2/16	3D Specialties
<p>This print is the exclusive property of Dakota Fence Co. and is not to be modified, photographed, scanned, or used by anyone without written consent from Dakota Fence Co. Failure to obtain permission may result in legal action.</p>			<p>FARGO, BISMARCK, MINOT, WILLISTON</p>
<p>MNDOT PSST and Breakaway Assembly</p>			<p>1110 25th Ave N. Fargo, ND 58107 Phone: (701) 237-6181 Fax: (701) 238-7811</p>
<p>VARIES</p>			<p>1915 20th St. S. Bismarck, ND 58502 Phone: (701) 258-9096 Fax: (701) 223-9140</p>
<p>6407 138th AVE NW Williston, ND 58702 Phone: (701) 852-0931 Fax: (701) 852-0931</p>			<p>6407 138th AVE NW Williston, ND 58702 Phone: (701) 826-6264 Fax: (701) 826-6264</p>



MEDIAN SIGN MOUNTING DETAIL 2

DRAWN: R.L.S.	DATE: 2/14/2017	SCALE: NONE	PLATE NO. STR-20
---------------	-----------------	-------------	------------------